



NT 65/2 Ap

Väkivahva märkä-kuivaimuri kahdella moottorilla, 65 litran säiliöllä sekä puoliautomaattisella suodattimen ravistuksella.

1 Imuletku kahvalla

- Imuletkun kätevä kiinnitys kahvasta imuriin kuljetuksen ja varastoinnin ajaksi.

2 Kumipintainen säilytystaso

- Iso säilytystaso josta esimerkiksi työkalut ja pesuaineet kätevästi saatavilla.

3 Integroitu poistoletku (öljynkestävä)

- Helppokäyttöinen tyhjennysletku kätevään nesteen tyhjennykseen.

4 ApClean - puoliautomaattinen suodattimen puhdistus

- Vapaa suodatin tarkoittaa sitä, että käyttäjä voi työskennellä pitkiä aikoja keskeytyksettä.
- Optimaalinen imuteho korkealla hyötysuhteella.



NT 65/2 Ap

- Puoliautomaattinen suodattimen puhdistus
- Laakasuodatin, pölypuokka M
- Tyhjennysletku ja työntöaisa

Tekniset tiedot

Tuotenumero	1.667-291.0	
EAN koodi	4039784727281	
Ilman läpivirtaus	l/s	2 x 74
Alipaine	mbar / kPa	254 / 25,4
Säiliötilavuus	l	65
Maks. ottoteho	W	max. 2760
Varusteiden halkaisija ID 51/61		ID 40
Johdon pituus	m	10
Äänvoimakkuus	dB(A)	73
Säiliön materiaali		Muovi
Moottoreiden lukumäärä		2
Taajuus	Hz	50-60
Jännite	V	220-240
Paino	kg	20
Mitat (p x l x k)	mm	600 x 480 x 920

Laite

Imuletku	m	4	Työntöaisa	■
Imutangot metallia, 2 x 0,5 m		■	Turvallisuusluokitus	II
Pölypussi		Paperi	Säiliön pyörä seisontajarrulla	■
Lattiasuulake märkä- ja kuivaimuointiin, 360 mm	mm	360	Huoltovapaat imumoottorit	kpl 2
Rakosuutin		■		
Tyhjennysletku (öljynkestävä)		■		
Automaattinen pinnanvartija säiliön täyttyessä		■		
Laakasuodatin		Paperi		
Imukahva		■		
Suodattimen puhdistus		ApClean - puoliautomaattinen suodattimen puhdistus		
Puskuri		■		

■ Toimituksen mukana.

NT 65/2 AP 1.667-291.0

KÄRCHER



			Tuotenumero	Määrä		Pituus	Leveys	Kuvaus	
Laakasuodatin (paperi)									
Laakasuodatin NT 65/2Eco	1	6.904-283.0	1 kpl					Paper flat pleated filter (BIA-(U,S,G,C) dust class M) suitable for NT 65/2 Eco, NT 65/2 Eco Tc, NT 65/2 Eco Me.	■
Paperinen pölypussi (kaksinkertainen)									
PÖLYPUSSI NT 65/2 Eco	2	6.904-285.0	5 kpl					5 3-ply, tear-resistant paper filter bags. BIA-(U, S, G, C) dust class M. For all NT 48/1, NT 65/2 Eco + Me and NT 72/2 Eco Tc models.	■
Taivutettu imutanko, muovia									
Taivutettu tanko DN 40, muovi	3	5.031-904.0	1 kpl	ID 40				Plastic bend (DN 40) with C-40 clip system, suitable for all NT models.	■
Taivutettu tanko DN 35, muovi	4	5.031-718.0	1 kpl	ID 35				Plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models (except NT Eco M and NT Eco H).	□
Taivutettu tanko DN 35, muovi, sähköä johtava	5	5.031-939.0	1 kpl	ID 35				Electrically conductive plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models.	□
Taivutettu tanko DN 40, muovi, sähköä johtava	6	5.032-427.0	1 kpl	ID 40				Electrically conductive plastic bend (DN 40) with C-40 clip system, suitable for all NT vacuum cleaners.	□
Lattiasuulakkeet									
Floor tool packaged basalt grey DN40	7	6.907-408.0	1 kpl	ID 40		360 mm			■
LAITOSSUUTIN GRD 370	8	6.903-018.0	1 kpl	ID 40		370 mm		All-purpose aluminium nozzle with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	□
LATTIASUULAKE DN40	9	6.906-383.0	1 kpl	ID 40		450 mm		All-purpose aluminium nozzle (DN 40) with 450 mm working width. With height-adjustable side rollers, brush strips (6.903-065.0) and oil-resistant squeegees (6.906-146.0). Only for NT vacuum cleaners.	□
LATTIASUULAKE DN 35	10	6.906-384.0	1 kpl	ID 35		370 mm		All-purpose aluminium nozzle (DN 35) with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	□
Rakosuulakkeet									
RAKOSUUTIN NW 40	11	6.903-033.0	1 kpl	ID 40	290 mm			Plastic crevice tool (DN 40) for vacuuming in crevices and corners. Length: 290 mm.	■
RAKOSUUTIN, NW 35	12	6.900-385.0	1 kpl	ID 35	210 mm			Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 210 mm.	□
RAKOSUUTIN METALLISTA	13	6.900-922.0	1 kpl	ID 35	500 mm			Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 370 mm.	□
RAKOSUUTIN	14	6.905-817.0	1 kpl	ID 40	400 mm			Metal crevice tool (DN 40) for vacuuming in crevices and corners. Length: 400 mm.	□
Imutangot metallia									
Imutanko, 0,5m, metallia/ ID 40	15	6.900-275.0	1 kpl	ID 40	0,55 m			Chromium-plated metal suction tube (DN 40, 1x0.5 m), standard for virtually all two-motor industrial vacuum cleaners. Optional for industrial single-motor NT vacuum cleaners with DN 40 suction hose.	■
IMUPUTKI NW 35, 0,5	16	6.900-514.0	1 kpl	ID 35	0,5 m			Chromium-plated metal suction tube (DN 35, 1x0.5 m), standard for virtually all single-motor industrial NT vacuum cleaners.	□
Imuletkut (Clip-system)									
Imuletku 4 m clip-system	17	6.906-321.0	1 kpl	40	4 m			4 m suction hose with bayonet and C 40 clip connection. Without bend and adapter.	■

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

NT 65/2 AP 1.667-291.0

KÄRCHER



		Tuotenumero	Määrä		Pituus	Leveys		Kuvaus		
Imuletku 10 m clip-system	18	6.906-279.0	1 kpl	40	10 m			10 m standard suction hose without bend and adapter. With bayonet at vacuum end and C 40 clip connection at accessory end.	<input type="checkbox"/>	
Imuletku 4 m, öljyn kestävä, clip-system	19	6.906-714.0	1 kpl	40	4 m			With bayonet and clip connection.	<input type="checkbox"/>	
Imuletku 4 m, clip-system, sähköä johtava	20	6.906-546.0	1 kpl	40	4 m			Sähköä johtava. 4 m imuletku bajonet-liitännällä ja C 40 clip-system pikakiinnityksellä. Mutka ja adapteri eivät sisälly toimitukseen. Huom! Ilman erillistä sovitinta, imuletku ei ole yhteensopiva 1-moottoristen imureiden vakiovarusteiden kanssa.	<input type="checkbox"/>	
Imuletku 16 m, clip-system	21	6.906-635.0	1 kpl	40	16 m			With bayonet and clip connection.	<input type="checkbox"/>	
Imuletku 4 m, clip-system, sähköä johtava	22	6.906-877.0	1 kpl	40	10 m			Suction hose with bayonet coupling, electrically conductive.	<input type="checkbox"/>	
Imuletkut täydellinen (Clip-system)										
Imuletku 4 m, (Clip-system)	23	4.440-678.0	1 kpl	ID 40	4 m			4 m electrically non-conductive suction hose with bend, bayonet at vacuum end and C 40 clip connection at accessory end. Without module.	<input checked="" type="checkbox"/>	
	24	4.440-679.0	1 kpl	ID 40	4 m			4 m electrically non-conductive suction hose with bend (C-DN 40) and module (4.060-474.0), bayonet at vacuum end and C 35 clip connection at accessory end.	<input type="checkbox"/>	
Imuletku 4 m, (Clip-system), sähköä johtava	25	4.440-728.0	1 kpl	ID 40	4 m			With bend and module (4.060-533.0), electrically conductive.	<input type="checkbox"/>	
Laakasuodatin (PES)										
Laakasuodatin, (PES) , pölyluokka M	26	6.904-284.0	1 kpl					Flat filter (PES) - BIA-(U,S,G,C) dust class M: rotproof polyester fleece, ideal for wet use and abrasives. Standard for NT 72/2 Eco Tc.	<input type="checkbox"/>	
Laakasuodatin (PTFE)										
Flat-pleated filter packaged PTFE	27	6.907-449.0	1 kpl						<input type="checkbox"/>	
Kangassuodatin										
Membraanisuodatin /polyester-fleece	28	6.904-282.0	1 kpl					Polyester needle fleece membrane/fabric filter - BIA-C -, washable up to 40°C, metal fibres for earthing. Suitable for virtually all industrial two-motor NT vacuum cleaners.	<input type="checkbox"/>	
HEPA-suodatin, pölyluokka H										
HEPA laakasuodatin	29	6.904-364.0	1 kpl					HEPA surface filter - dust class H (H 14) - with glass-fibre layers increases filter capacity when vacuuming health-endangering and carcinogenic dust.	<input type="checkbox"/>	
Muovisäkit										
Muovisäkki NT 7xx 110 kpl	30	6.900-698.0	10 kpl					PE plastic sack.	<input type="checkbox"/>	
Erikoispölypussi, märkäimurointi										
Erikoispölypussi märkäimurointiin	31	6.904-252.0	5 kpl					Approved for dust class L, general cleaning, wet and dry, tear-resistant.	<input type="checkbox"/>	
Taivutetut imutangot, rosteria										
Taivutettu tanko DN 35, RST	32	6.903-141.0	1 kpl	ID 35				Stainless steel and crooked, ID 35	<input type="checkbox"/>	
Taivutettu tanko DN 40, RST	33	6.902-079.0	1 kpl	ID 40				Stainless steel and crooked, ID 40	<input type="checkbox"/>	
Taivutetut imutangot, metallia										
Taivutettu tanko, metallia ID 35	34	6.900-519.0	1 kpl	ID 35				Robust, chromium-plated metal bend (DN 35), can be used instead of a plastic bend (with clip system adapter 5.407-112.0; C 35-DN 35, plastic, el).	<input type="checkbox"/>	
Taivutettu tanko, metallia ID 40	35	6.900-276.0	1 kpl	ID 40				Robust, chromium-plated metal bend (DN 40), can be used instead of a plastic bend (with clip system adapter 5.407-111.0; C 40-DN 40, plastic, el).	<input type="checkbox"/>	

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

NT 65/2 AP 1.667-291.0

KÄRCHER



		Tuotenumero	Määrä		Pituus	Leveys		Kuvaus		
Autonimurointisuulakkeet										
AUTOSUUTIN_JATKOSSA 6.906-255	36	6.900-952.0	1 kpl	ID 40		90 mm		Angled, flat, plastic car vacuuming tool with about 90 mm working width. Only for NT vacuum cleaners.		<input type="checkbox"/>
Imusuulake, kumikärki 45°										
Kumisuuulake, DN 35 45° kärki	37	6.902-104.0	1 kpl	ID 35	220 mm			45° rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.		<input type="checkbox"/>
Kumisuuulake, DN 40, 45° kärki	38	6.902-105.0	1 kpl	ID 40	220 mm			45° rubber suction nozzle (DN 40), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.		<input type="checkbox"/>
Putkisuulakkeet										
PUTKISUUTIN 100 MM	39	6.903-035.0	1 kpl	ID 35				Plastic, pipe diameter 100 mm		<input type="checkbox"/>
PUTKISUUTIN 200 MM	40	6.903-036.0	1 kpl	ID 35				Plastic, pipe diameter 200 mm		<input type="checkbox"/>
Imutangot, ruostumaton teräs										
Imutanko, 0,5 m RST DN 40	41	6.902-081.0	1 kpl	ID 40	0,5 m			Stainless steel suction tube (DN 40, 0.5 m) only suitable for NT vacuum cleaners.		<input type="checkbox"/>
Imutanko, 1 m RST DN 40	42	6.906-531.0	1 kpl	ID 40	1 m			Stainless steel suction tube (DN 40, 1.0 m) only suitable for NT vacuum cleaners.		<input type="checkbox"/>
Imutanko DN 35	43	6.902-154.0	1 kpl	ID 35	0,5 m					<input type="checkbox"/>
Korjaussarjat										
Korjaussetti	44	2.639-873.0	1 kpl	ID 40				Repair set (C40) includes threaded hose adapters (without bayonet adapter) for industrial NT vacuum cleaners with clip system.		<input type="checkbox"/>
	45	2.862-038.0	1 kpl	ID 61				Suction hose repair kit. Optional for all NT 65/2 and 72/2, NT 993 I, NT 802 I.		<input type="checkbox"/>
Imuletkut (ilman liittimiä)										
	46	6.389-839.0						(without connectors)		<input type="checkbox"/>
Imuletkut täydellinen										
Imuletku 4 m	47	4.440-264.0	1 kpl	ID 61	4 m			4-m standard suction hose with DN 61 bayonet connector at the device end and DN 61 tapered connector at the accessory end.		<input type="checkbox"/>
Imuletku, teräsvahvistettu teollisuuslaatu	48	4.440-328.0	1 kpl	ID 61	3 m					<input type="checkbox"/>
Imuletku 10 m	49	4.440-467.0	1 kpl	ID 61	10 m			10-m standard suction hose with DN 61 bayonet connector at the device end and DN 61 tapered connector at the accessory end.		<input type="checkbox"/>
Imuletku 4 m, öljynkestävä	50	4.440-613.0	1 kpl	ID 61	4 m			Oil-resistant.		<input type="checkbox"/>
Imuletku 10 m, öljynkestävä	51	4.440-614.0	1 kpl	ID 61	10 m					<input type="checkbox"/>
Imuletku 4 m, sähköä johtava	52	4.440-616.0	1 kpl	ID 61	4 m					<input type="checkbox"/>
Imuletku 4 m	53	4.440-263.0	1 kpl	ID 40	4 m			Electrically non-conductive 4.0m standard suction hose with bayonett at vacuum end and DN 40 cone at accessory end.		<input type="checkbox"/>
Imuletku 4 m, öljynkestävä	54	4.440-303.0	1 kpl	ID 40	4 m			Oil-resistant		<input type="checkbox"/>
Imuletku 10 m	55	4.440-463.0	1 kpl	ID 40	10 m			Electrically non-conductive 10.0m standard suction hose with bayonett at vacuum end and DN 40 cone at accessory end.		<input type="checkbox"/>
Imuletku 10 m, sähköä johtava	56	4.440-466.0	1 kpl	ID 40	10 m			Electrically conductive, 10.0m, ID 40		<input type="checkbox"/>
Imuletku 10 m, öljynkestävä	57	4.440-612.0	1 kpl	ID 40	10 m			Oil-resistant.		<input type="checkbox"/>

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

NT 65/2 AP 1.667-291.0

KÄRCHER


		Tuotenumero	Määrä	ID	Pituus	Leveys		Kuvaus		
Sovitinkappaleet										
Letkujen liitospäälle	58	6.902-077.0	1 kpl	ID 32				Electrically non-conductive adapter with internal thread. For connecting two suction hoses without connectors. Suitable for DN 32 or DN 35.	<input type="checkbox"/>	
	59	6.900-286.0	1 kpl	ID 40				Electrically non-conductive adapter with screw thread at both ends. For connecting 2 DN 40 suction hoses without connectors.	<input type="checkbox"/>	
	60	6.902-078.0	1 kpl	ID 61					<input type="checkbox"/>	
Jatkoletkut (Clip-system)										
Jatkoletku (clip-system) 2,5 m	61	6.906-344.0	1 kpl	ID 40	2,5 m			2,5 m electrically non-conductive standard extension hose for all C-40 hoses with clip system.	<input type="checkbox"/>	
Sonstiges										
Esierotin	62	3.864-010.0	1 kpl						<input type="checkbox"/>	
Esierotin, metalli DN 61	63	3.864-012.0	1 kpl						<input type="checkbox"/>	
Kansi esierottimeen	64	4.063-132.0	1 kpl						<input type="checkbox"/>	
CS 40 Me	65	2.863-026.0	1 kpl						<input type="checkbox"/>	
Y-liitinsetti										
Y-kappalesetti, muovia	66	2.637-217.0	1 kpl	ID 35				Plastic distributor - suitable for NT vacuum cleaners.	<input type="checkbox"/>	
Sovitin C ID, antistaattinen										
Liitospäälle C-DN35 (sähköä johtava)	67	5.407-112.0	1 kpl	ID 35				C 35 hose connector for DN 35 accessory, electrically conductive.	<input type="checkbox"/>	
Liitospäälle C40-DN35	68	5.407-109.0	1 kpl	ID 40				Electrically conductive adapter (C 40) with DN 35 connection for connecting DN 35 accessories to an industrial C 40 or C-DN 40 suction hose. Suitable for NT vacuum cleaners.	<input type="checkbox"/>	
Liitospäälle C-DN40	69	5.407-111.0	1 kpl	ID 40				C 40 hose connector for DN 40 accessory, electrically conductive.	<input type="checkbox"/>	
Sovitin sähkötyökaluille, clip-kiinnitys, antistaattinen										
SÄHKÖTYÖKALUADAPTERI	70	5.453-042.0	1 kpl	ID 35				3-way plastic adapter. For DN 26 to DN 36. For connecting power tools to an industrial C or C-DN 35 suction hose. Suitable for NT vacuum cleaners.	<input type="checkbox"/>	
Liitospäälle, sähkötyökalulle	71	5.453-048.0	1 kpl	ID 35				Inside Ø 25.4 mm, outside Ø 34.6 mm/ 38 mm, electrically conductive. Only NT vacuums.	<input type="checkbox"/>	
	72	5.453-049.0	1 kpl	ID 35					<input type="checkbox"/>	
	73	5.453-050.0	1 kpl	ID 35				Inside Ø 27 mm, outside Ø 36.5 mm/38.8 mm, electrically conductive. Only NT vacuums.	<input type="checkbox"/>	
	74	5.453-051.0	1 kpl	ID 35					<input type="checkbox"/>	
	75	5.453-052.0	1 kpl	ID 35					<input type="checkbox"/>	
Sovitin sähkötyökaluille, kierteellä										
Adapteri sähkötyökalulle	76	5.453-016.0	1 kpl	ID 35				3-way plastic adapter with fitting instructions. For DN 26 to DN 36. For connecting to an industrial DN 35 suction hose.	<input type="checkbox"/>	
	77	5.453-026.0	1 kpl	ID 35				Inside Ø 28.6 mm, outside Ø 37.3/38.8 mm.	<input type="checkbox"/>	
	78	6.902-059.0	1 kpl	ID 35				Electrically conductive power tool adapter, threaded. Internal diameter: 32 mm. External diameter: 39 mm.	<input type="checkbox"/>	
	79	6.902-095.0	1 kpl	ID 35				2-way power tool adapter, threaded. For connecting to an industrial DN 35 suction hose. Internal diameter: 28 mm. External diameter: 34 mm and 38.8 mm. Suitable for NT vacuum cleaners.	<input type="checkbox"/>	
Sovitin (putkisuutin)										
Sovitin DN 40-61	80	5.453-019.0	1 kpl	ID 40				From DN 40 to DN 61: Plastic adapter (electrically non-conductive). Suitable for NT vacuum cleaners.	<input type="checkbox"/>	

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

NT 65/2 AP 1.667-291.0

KÄRCHER



		Tuotenumero	Määrä		Pituus	Leveys		Kuvaus		
Supistin										
Supistin C40	81	5.407-108.0	1 kpl	ID 40				Threaded reducer - from C-40 to DN 35. Suitable for NT vacuum cleaners.		<input type="checkbox"/>
BUSHING	82	5.407-113.0	1 kpl	ID 40				Reducer (C 40 to C 35) for connecting accessories with C-35 clip connection to suction hoses with C 40 clip system.		<input type="checkbox"/>
Supistin (putki - suutin)										
Supistin DN40 - DN35	83	6.902-017.0	1 kpl	ID 40				Reducer for accessory extension. Ideal for accessories with DN 35 connecting cone in combination with accessories with DN 40 connecting cone.		<input type="checkbox"/>
Supistin DN35 - DN32	84	6.902-072.0	1 kpl	ID 35				Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners.		<input type="checkbox"/>
Supistin ja jatko-osasetti										
Supistin/sovitinsetti ID40/35, 35/32 muovia	85	2.860-117.0	1 kpl					DN 40/35, DN 35/32 (tube -> nozzle), plastic.		<input type="checkbox"/>
Varustesetit imureihin										
Profi-setti ID 40	86	2.637-353.0		ID 40				Individual parts: Suction hose 4 m (4.440-263.0), bend, metal (6.900-276.0), suction tube 2 x 0.5 m, metal (6.900-275.0), grout nozzle (6.903-033.0), floor nozzle with rollers (6.903-051.0).		<input type="checkbox"/>
Auton imurointisetti ID 36	87	2.862-166.0		ID 35				Target group-specific accessory nozzles in DN 35 for interior cleaning of vehicles, upholstery & fixtures.		<input type="checkbox"/>
Teollisuussetti ID 61	88	2.637-355.0		ID 61				Target group-specific robust complete accessory set in DN 61 for vacuuming coarse dirt in industry, construction etc.		<input type="checkbox"/>
Askartelusetti	89	2.640-760.0		ID 61						<input type="checkbox"/>
Bussin imurointisetti ID 40 NT 65/2	90	2.640-560.0		ID 40				Accessory kit for vacuuming and cleaning buses, train compartments, etc., in combination with the recommended NT vacuum cleaner.		<input type="checkbox"/>
UBS sähköä johtamaton										
	91	2.642-602.0	1 kpl							<input type="checkbox"/>

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

NT 65/2 AP 1.667-291.0

KÄRCHER



		Tuotenumero	Pituus		Määrä		Kuvaus	
Sekalaiset								
Jatkojohto	1	6.647-022.0	20 m		1 kpl		Extension cable, 20 m, 3x1.5 mm ² . With splash-proof earthing pin plug, strain relief and anti-kink sleeve.	<input type="checkbox"/>

■ Toimituksen mukana. Saatavilla olevat varusteet.

NT 65/2 AP 1.667-291.0

KÄRCHER



		Tuotenumero	Määrä		Pituus/ Leveys			Kuvaus	
Lattiasuulakkeet									
Lattiasuulake 500 mm	1	4.130-413.0	1 kpl	ID 61	500 mm			Aluminium, oil-proof, 500 mm, with hight-adjustable rollers, strips (6.903-067.0) and rubber lips (6.906-168.1)	<input type="checkbox"/>
Muut suulakkeet									
Kuminen suulake 45° DN61	2	6.902-106.0	1 kpl	ID 61	220 mm			Angled 45°, for suction of machines, oil-resistant	<input type="checkbox"/>
Raaputin metallia	3	6.903-360.0	1 kpl	ID 61	104 mm			Scratcher and scraper tool DN 61, sheet metal, 117 mm	<input type="checkbox"/>
Tasopintojen suulake alu DN 61 200 mm	4	4.130-415.0	1 kpl	ID 61	200 mm			Flat surface nozzle cpl. DN 51, 200 mm, aluminium with brush and stainless steel bumper	<input type="checkbox"/>
Rakosuulakkeet									
Saumalaastisuulake 370 mm syntetttinen	5	6.900-222.0	1 kpl	ID 61	370 x 64 mm			Grout nozzle, plastic, 370 mm	<input type="checkbox"/>
Liittimet ja varaosat									
Vacuuum cleaner connection DN61 auf DN52	6	6.902-002.0	1 kpl	ID 52					<input type="checkbox"/>

■ Toimituksen mukana. □ Saatavilla olevat varusteet.