



NT 27/1 Adv

NT 27/1 Advanced on monipuolinen ja tehokas kompaktisarjan imuri pienehköjen alueiden siivoukseen.

1 Patruunasuodatin koholla

- Patruunasuodattimen suuri pinta-ala mahdollistaa pitkäaikaisen työskentelyn. Mekaaninen nestepintaa vartioiva koho keskeyttää imutoiminnon kun säiliön maksimitäyttömäärä on saavutettu.

2 Vahvat metalliklipsit

- Takaavat luotettavan lukituksen.

3 Suojapuskuri

- Säiliön ympärillä törmäyssuoja joka suojaa sekä laitetta, että seinä, kalusteita tai muita laitteita kolhuilta.



NT 27/1 Adv

- Patruunasuodatin jossa laaja suodatinala
- Muovinen säiliö
- Leveä märkäimurointisuulake

Tekniset tiedot

Tuotenumero	1.428-520.0	
EAN koodi	4039784724327	
Virtatyyppi	V / Hz	220 - 240 / 50 - 60
Ilman läpivirtaus	l/s	67
Alipaine	mbar / kPa	200 / 20
Säiliötilavuus	l	27
Säiliön materiaali		muovi
Moottoriteho	W	max. 1380
Varusteiden halkaisija		ID 35
Virtajohdon pituus	m	7,5
Äänenvoimakkuus	dB(A)	72
Moottoreiden lukumäärä		1
Paino	kg	7,5
Mitat (p x l x k)	mm	420 x 420 x 525

Laite

Imuletku	m	2,5
Imuputki	kpl / m	2 x 0,5 / Metalli
Pölypussi		Paperi
Kpl-määrä	kpl	1
Lattiasuulake märkä- ja kuivaimurointiin	mm	400
Rakosuulake		■
Patruunasuodatin		■
Patruunasuodatin		Paperi
Puskuri		■
Turvallisuusluokitus		II
■ Toimituksen mukana.		

NT 27/1 ADV

1.428-520.0

KÄRCHER


		Tuotenumero	Määrä		Pituus	Leveys	Hinta	Kuvaus		
Patruunasuodatin, paperi										
Cartridge filter	1	6.414-789.0	1 kpl					Paper cartridge filter with larger filter surface, standard for NT 48/1 and optional for NT 27/1/Me Advanced.	■	
Taivutettu imutanko, muovia										
Taivutettu tanko DN 35, muovi	2	5.031-718.0	1 kpl	ID 35				Plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models (except NT Eco M and NT Eco H).	■	
Taivutettu tanko DN 35, muovi, sähköä johtava	3	5.031-939.0	1 kpl	ID 35				Electrically conductive plastic bend (DN 35) with C-35 clip system. For all industrial single-motor NT 361 to NT 611 Eco models.	□	
Taivutettu tanko DN 35, muovi	4	6.902-009.0	1 kpl	ID 35				Plastic, ID 35.	□	
Taivutettu tanko DN 40, muovi, sähköä johtava	5	5.032-427.0	1 kpl	ID 40				Electrically conductive plastic bend (DN 40) with C-40 clip system, suitable for all NT vacuum cleaners.	□	
Taivutettu tanko DN 40, muovi	6	5.031-904.0	1 kpl	ID 40				Plastic bend (DN 40) with C-40 clip system, suitable for all NT models.	□	
Lattiasuulakkeet										
	7	2.889-118.0	1 kpl	ID 35		400 mm			■	
LATTIASUULAKE DN35	8	6.906-512.0	1 kpl	ID 35		300 mm		All-purpose plastic nozzle (DN 35) with 300 mm working width. With side rollers, brush strips (6.903-278.0) and squeegees (6.903-277.0). Only for NT vacuum cleaners.	□	
LAITOSSUUTIN GRD 370	9	6.903-018.0	1 kpl	ID 40		370 mm		All-purpose aluminium nozzle with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	□	
LATTIASUULAKE DN40	10	6.906-383.0	1 kpl	ID 40		450 mm		All-purpose aluminium nozzle (DN 40) with 450 mm working width. With height-adjustable side rollers, brush strips (6.903-065.0) and oil-resistant squeegees (6.906-146.0). Only for NT vacuum cleaners.	□	
LATTIASUULAKE DN 35	11	6.906-384.0	1 kpl	ID 35		370 mm		All-purpose aluminium nozzle (DN 35) with 370 mm working width. With height-adjustable side rollers, brush strips (6.903-064.0) and oil-resistant squeegees (6.903-081.0). Only for NT vacuum cleaners.	□	
Floor tool packaged basalt grey DN40	12	6.907-408.0	1 kpl	ID 40		360 mm			□	
Rakosuulakkeet										
RAKOSUUTIN, NW 35	13	6.900-385.0	1 kpl	ID 35	210 mm			Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 210 mm.	■	
Crevice nozzle DN35	14	6.906-240.0	1 kpl	ID 35	250 mm			Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 250 mm.	■	
RAKOSUUTIN METALLISTA	15	6.900-922.0	1 kpl	ID 35	500 mm			Plastic crevice tool (DN 35) for vacuuming in crevices and corners. Length: 370 mm.	□	
RAKOSUUTIN NW 40	16	6.903-033.0	1 kpl	ID 40	290 mm			Plastic crevice tool (DN 40) for vacuuming in crevices and corners. Length: 290 mm.	□	
RAKOSUUTIN	17	6.905-817.0	1 kpl	ID 40	400 mm			Metal crevice tool (DN 40) for vacuuming in crevices and corners. Length: 400 mm.	□	
Imutangot metallia										
IMUPUTKI NW 35, 0,5	18	6.900-514.0	1 kpl	ID 35	0,5 m			Chromium-plated metal suction tube (DN 35, 1x0.5 m), standard for virtually all single-motor industrial NT vacuum cleaners.	■	
Imutanko, 0,5m, metallia/ ID 40	19	6.900-275.0	1 kpl	ID 40	0,55 m			Chromium-plated metal suction tube (DN 40, 1x0.5 m), standard for virtually all two-motor industrial vacuum cleaners. Optional for industrial single-motor NT vacuum cleaners with DN 40 suction hose.	□	

■ Toimituksen mukana. □ Saatavilla olevat varusteet.



		Tuotenumero	Määrä		Pituus	Leveys	Hinta	Kuvaus	
Imuletkut täydellinen (Clip-system)									
IMULETKU+TAIVUTETTU IMUTANKO	20	4.440-626.0	1 kpl	ID 35	2,5 m			2.5 m standard suction hose with bend, bayonet at vacuum end and C 35 clip connection at accessory end. Without PDFC module. Standard for NT 27/1/Me Advance und NT 48/1.	■
Imuletku 2,5 m, (Clip-system), sähköä johtava	21	4.440-653.0	1 kpl	ID 35	2,5 m			2.5 m electrically conductive suction hose with bend, bayonet at vacuum end and C 35 clip connection at accessory end. Without module.	□
Sovitin sähkötyökaluille, clip-kiinnitys, antistaattinen									
SÄHKÖTYÖKALUADAPTERI	22	5.453-042.0	1 kpl	ID 35				3-way plastic adapter. For DN 26 to DN 36. For connecting power tools to an industrial C or C-DN 35 suction hose. Suitable for NT vacuum cleaners.	■
Liitoskappale, sähkötyökalulle	23	5.453-048.0	1 kpl	ID 35				Inside Ø 25.4 mm, outside Ø 34.6 mm/ 38 mm, electrically conductive. Only NT vacuums.	□
	24	5.453-049.0	1 kpl	ID 35					□
	25	5.453-050.0	1 kpl	ID 35				Inside Ø 27 mm, outside Ø 36.5 mm/38.8 mm, electrically conductive. Only NT vacuums.	□
	26	5.453-051.0	1 kpl	ID 35					□
	27	5.453-052.0	1 kpl	ID 35					□
Mikrosuihkusetit									
SUUTINSARJA NW35	28	2.860-116.0	1 kpl	ID 35				Nozzle kit for all NT vacuum cleaners with DN 35 accessories includes crevice tool, upholstery tool, round brush (x3)	□
Kangassuodatin									
Membraanisuo-datin /kangassuo-datin NT 351	29	6.906-103.0	1 kpl					Polyester needle fleece membrane/fabric filter, washable up to 40°C. For NT 27/1/Me Advance, NT 48/1, NT 351 Eco/ Professional.	□
Paperinen pölypusi (kaksinkertainen)									
PÖLYPUSSI 5 KPL\ NT 27\1	30	6.904-290.0	5 kpl					5 paper filter bags. BIA-(U, S, G, C) dust class M. Suitable for NT 27/1/Me Advanced.	□
Erikoispölypusi, märkäimurointi									
Pölypusi märkä-kuivaimurointiin NT 361, 5 kpl	31	6.904-171.0	5 kpl					Approved for dust class L, general cleaning, wet and dry, tear-resistant.	□
Taivutetut imutangot, rosteria									
Taivutettu tanko DN 35, RST	32	6.903-141.0	1 kpl	ID 35				Stainless steel and crooked, ID 35	□
Taivutettu tanko DN 40, RST	33	6.902-079.0	1 kpl	ID 40				Stainless steel and crooked, ID 40	□
Taivutetut imutangot, metallia									
Taivutettu tanko, metallia ID 35	34	6.900-519.0	1 kpl	ID 35				Robust, chromium-plated metal bend (DN 35), can be used instead of a plastic bend (with clip system adapter 5.407-112.0, C 35-DN 35, plastic, el).	□
Taivutettu tanko, metallia ID 40	35	6.900-276.0	1 kpl	ID 40				Robust, chromium-plated metal bend (DN 40), can be used instead of a plastic bend (with clip system adapter 5.407-111.0, C 40-DN 40, plastic, el).	□
Yleisharjat									
Yleisharja	36	6.900-425.0	1 kpl	ID 35	120 mm			All-purpose brush PPN_Bristle	□
Autonimurointisuulakkeet									
AUTOSUUTIN NW35	37	6.906-108.0	1 kpl	ID 35		90 mm		Angled, flat, plastic car vacuuming tool with about 90 mm working width. Only for NT vacuum cleaners.	□
Imusuulake, kumikärki 45°									
Kumisuulake, DN 35 45° kärki	38	6.902-104.0	1 kpl	ID 35	220 mm			45° rubber suction nozzle (DN 35), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	□
Kumisuulake, DN 40, 45° kärki	39	6.902-105.0	1 kpl	ID 40	220 mm			45° rubber suction nozzle (DN 40), oil-resistant and suitable for vacuuming machines. Only for NT vacuum cleaners.	□

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

NT 27/1 ADV 1.428-520.0

KÄRCHER



		Tuotenumero	Määrä		Pituus	Leveys	Hinta	Kuvaus		
Lattiasuulakkeet, kuivaimurointi										
Yhdistelmäsuulake (kuiva) ID 35, 270 mm	40	6.906-511.0	1 kpl	ID 35		270 mm		Combination floor tool with changeover function, plastic (272 mm). With stainless steel base plate, thread catcher 6.905-417.0 and DN 35 connection.		<input type="checkbox"/>
Putkisuulakkeet										
PUTKISUUTIN 100 MM	41	6.903-035.0	1 kpl	ID 35				Plastic, pipe diameter 100 mm		<input type="checkbox"/>
PUTKISUUTIN 200 MM	42	6.903-036.0	1 kpl	ID 35				Plastic, pipe diameter 200 mm		<input type="checkbox"/>
Harjasuulakkeet										
HARJASUUTIN NIVELÖITY 35mm	43	6.903-862.0	1 kpl	ID 35		70 mm		Rotatable suction brush (DN 35) with natural bristles (cow hair). Bristle size 70x45 mm. Only CV and NT vacuum cleaners.		<input type="checkbox"/>
Turbosuulakkeet										
TURBOSUUTIN/HUONEKALU	44	2.860-113.0	1 kpl	ID 32		160 mm		Plastic turbo upholstery nozzle (DN 35/32, 160 mm) with reduction sleeve.		<input type="checkbox"/>
TURBOSUUTIN/LATTIA	45	2.860-114.0	1 kpl	ID 32		270 mm		Plastic turbo floor nozzle (DN 35/32, 270 mm) with reduction sleeve.		<input type="checkbox"/>
Imutangot, ruostumaton teräs										
Imutanko, 0,5 m RST DN 40	46	6.902-081.0	1 kpl	ID 40	0,5 m			Stainless steel suction tube (DN 40, 0.5 m) only suitable for NT vacuum cleaners.		<input type="checkbox"/>
Imutanko, 1 m RST DN 40	47	6.906-531.0	1 kpl	ID 40	1 m			Stainless steel suction tube (DN 40, 1.0 m) only suitable for NT vacuum cleaners.		<input type="checkbox"/>
Imutanko DN 35	48	6.902-154.0	1 kpl	ID 35	0,5 m					<input type="checkbox"/>
Imutangot muovi										
Imutanko, 0,5 m, muovia/ ID 35	49	6.900-384.0	1 kpl	ID 35	0,5 m			Plastic suction tube (DN 35, 1x0.5 m) only suitable for BV and T vacuum cleaners.		<input type="checkbox"/>
Korjaussarjat										
Korjaussetti	50	2.639-682.0	1 kpl	ID 35				Repair set (C35) includes threaded hose adapters (without bayonet adapter) for industrial NT vacuum cleaners with clip system.		<input type="checkbox"/>
Imuletkut (Clip-system)										
Imuletku 4 m clip-system	51	6.906-241.0	1 kpl	35	4 m			4 m suction hose without bend and adapter. With bayonet at vacuum end and C 35 clip connection at accessory end.		<input type="checkbox"/>
Imuletku 2,5 m clip-system	52	6.906-275.0	1 kpl	35	2,5 m			2.5 m electrically conductive suction hose without bend and adapter with bayonet at vacuum end and C 35 clip connection at accessory end.		<input type="checkbox"/>
Imuletku 4 m clip-system	53	6.906-500.0	1 kpl	35	4 m			4 m electrically conductive suction hose without bend and adapter with bayonet at vacuum end and C 35 clip connection at accessory end.		<input type="checkbox"/>
Imuletkut täydellinen										
Imuletku 4 m	54	4.440-287.0	1 kpl	ID 35	4 m			Standard, 4.0m, ID 35		<input type="checkbox"/>
Sovitinkappaleet										
Letkujen liitoskappale	55	6.902-077.0	1 kpl	ID 32				Electrically non-conductive adapter with internal thread. For connecting two suction hoses without connectors. Suitable for DN 32 or DN 35.		<input type="checkbox"/>
Sovitin C ID, antistaattinen										
Liitoskappale C-DN35 (sähköä johtava)	56	5.407-112.0	1 kpl	ID 35				C 35 hose connector for DN 35 accessory, electrically conductive.		<input type="checkbox"/>
Liitoskappale C40-DN35	57	5.407-109.0	1 kpl	ID 40				Electrically conductive adapter (C 40) with DN 35 connection for connecting DN 35 accessories to an industrial C 40 or C-DN 40 suction hose. Suitable for NT vacuum cleaners.		<input type="checkbox"/>
Liitoskappale C-DN40	58	5.407-111.0	1 kpl	ID 40				C 40 hose connector for DN 40 accessory, electrically conductive.		<input type="checkbox"/>

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

NT 27/1 ADV 1.428-520.0

KÄRCHER



		Tuotenumero	Määrä		Pituus	Leveys	Hinta	Kuvaus	
Sovitin sähkötyökaluille, kierteellä									
Adaptteri sähkötyökalulle	59	5.453-016.0	1 kpl	ID 35				3-way plastic adapter with fitting instructions. For DN 26 to DN 36. For connecting to an industrial DN 35 suction hose.	<input type="checkbox"/>
	60	5.453-026.0	1 kpl	ID 35				Inside Ø 28.6 mm, outside Ø 37.3/38.8 mm.	<input type="checkbox"/>
	61	6.902-059.0	1 kpl	ID 35				Electrically conductive power tool adapter, threaded. Internal diameter: 32 mm.External diameter: 39 mm.	<input type="checkbox"/>
	62	6.902-095.0	1 kpl	ID 35				2-way power tool adapter, threaded. For connecting to an industrial DN 35 suction hose. Internal diameter: 28 mm. External diameter: 34 mm and 38.8 mmSuitable for NT vacuum cleaners.	<input type="checkbox"/>
Supistin									
Supistin C40	63	5.407-108.0	1 kpl	ID 40				Threaded reducer - from C-40 to DN 35. Suitable for NT vacuum cleaners.	<input type="checkbox"/>
BUSHING	64	5.407-113.0	1 kpl	ID 40				Reducer (C 40 to C 35) for connecting accessories with C-35 clip connection to suction hoses with C 40 clip system.	<input type="checkbox"/>
Supistin (putki - suutin)									
Supistin DN40 - DN35	65	6.902-017.0	1 kpl	ID 40				Reducer for accessory extension. Ideal for accessories with DN 35 connecting cone in combination with accessories with DN 40 connecting cone.	<input type="checkbox"/>
Supistin DN35 - DN32	66	6.902-072.0	1 kpl	ID 35				Reducer with internal connecting cone DN 32. Ideal for accessories from the industrial vacuum cleaner range in combination with industrial NT vacuum cleaners.	<input type="checkbox"/>
Supistin ja jatko-osasetti									
Supistin/sovitinsetti ID40/35, 35/32 muovia	67	2.860-117.0	1 kpl					DN 40/35, DN 35/32 (tube -> nozzle), plastic.	<input type="checkbox"/>
Muut									
Drilling dust tool	68	2.679-000.0	1 kpl						<input type="checkbox"/>
CS 40 Me	69	2.863-026.0	1 kpl						<input type="checkbox"/>

■ Toimituksen mukana. □ Saatavilla olevat varusteet.

NT 27/1 ADV 1.428-520.0

KÄRCHER



		Tuotenumero	Pituus	Väri	Määrä	Hinta	Kuvaus	
Sekalaiset								
Jatkojohto	1	6.647-022.0	20 m		1 kpl		Extension cable, 20 m, 3x1.5 mm ² . With splash-proof earthing pin plug, strain relief and anti-kink sleeve.	<input type="checkbox"/>

■ Toimituksen mukana. Saatavilla olevat varusteet.